

MarkPro TWOi Software Update Procedure

A computer with a USB port and a MIDI file player application, such as Microsoft's Media Player, is required to perform the update (alternatively, updates can be done via MIDI using a traditional MIDI interface connected to your computer, feeding the ProTWOi MIDI In). The update file itself may be downloaded from the Kurzweil website:

<http://www.kurzweilmusicsystems.com/Downloads.php>

● How to Update the **Operating System Software**:

1. Using a standard USB cable, connect the MarkPro TWOi to your computer. (or make connections via traditional MIDI i/o)
2. Turn the MarkPro TWOi power on.
3. Dots in the LED display will blink for 3 seconds.
4. Press the **Global** button while the LED dots blink (this puts you into a special system mode known as the "Bootblock".)
5. The screen will display: "UoS"
6. Press the **Transpose +** button.
7. The LED dots will blink and the screen will display: "U.o.S."
8. The MarkPro TWOi is now ready to receive the **OS** update.
9. Using Media Player (or similar) in your computer, open the **OS** update file.
10. Select Play in Media Player to send the coded data to the MarkPro TWOi. Within 5 seconds the **Global** LED should begin blinking. This is your indication that the MarkPro TWOi is receiving the **OS** update data.
11. The update file will take about **19 minutes** to play completely. The **Global** LED should continue to blink during this time.
12. When the file has finished playing into the MarkPro TWOi, the screen will display: "o } " (meaning "ok") signifying the installation is complete". Turn the MarkProTWOi power off, wait 5 seconds, then turn it on again.
13. Lastly, reset the MarkProTWOi. Do this by striking the C8 key (rightmost on the keyboard) while holding the **Global** button down.

/end