

Mark-Pro TWOi Boot Loader Update Procedure

A computer with a USB port and a MIDI file player application, such as Microsoft's Media Player, is required to perform the update (alternatively, updates can be done via MIDI using a traditional MIDI interface connected to your computer, feeding the ProTWOi MIDI In). The update file itself may be downloaded from the Kurzweil website:

<http://www.kurzweilmusicsystems.com/Downloads.php>

● How to Update the **Boot loader** Software:

1. Using a standard USB cable, connect the MarkPro TWOi to your computer. (or make connections via traditional MIDI i/o)
2. Turn the MarkPro TWOi power on.
3. Dots in the LED display will blink for 3 seconds.
4. Press the **Global** button while the LED dots blink (this puts you into a special system mode known as the "Bootblock".)
5. The screen will display: "UoS"
6. Press the **+/Yes** button.
7. The screen will display: "Ubt".
8. Press the **Transpose +** button.
9. The LED dots will blink and the screen will display: "U.b.t.".
10. The MarkPro TWOi is now ready to receive the **Boot loader** update.
11. Using Media Player (or similar) in your computer, open the **Boot loader** update file.
12. Select Play in Media Player to send the coded data to the MarkPro TWOi. Within 5 seconds the **Global** LED should begin blinking. This is your indication that the MarkPro TWOi is receiving the **Boot Loader** update data.
13. The update file will take about **3 minutes** to play completely. The **Global** LED should continue to blink during this time.
14. When the file finishes playing into the MarkPro TWOi completely, the unit will boot back into normal operating mode automatically.

Need be, proceed to install any necessary OS updates.

/end